

Package: seasonalview (via r-universe)

September 14, 2026

Type Package

Title Graphical User Interface for Seasonal Adjustment

Version 1.0.0

Description A graphical user interface to the 'seasonal' package and 'X-13ARIMA-SEATS', the U.S. Census Bureau's seasonal adjustment software.

Depends R (>= 3.0.0), seasonal (>= 1.10.0)

Encoding UTF-8

Imports shinydashboard (>= 0.5.3), shiny (>= 0.14), dygraphs (>= 1.1.1.3), htmlwidgets, openxlsx, xtable, xts, zoo

License GPL-3

URL <http://www.seasonal.website>

BugReports <https://github.com/christophsax/seasonalview/issues>

RoxygenNote 7.3.2

Config/pak/sysreqs cmake make libicu-dev libuv1-dev zlib1g-dev

Repository <https://christophsax.r-universe.dev>

Date/Publication 2024-10-21 14:13:10 UTC

RemoteUrl <https://github.com/christophsax/seasonalview>

RemoteRef HEAD

RemoteSha b2e309127c06989fcf2048d2097ea7bb761b9a1f

Contents

seasonalview-package	2
standalone	2
view	3

Index	5
--------------	----------

seasonalview-package *Graphical User Interface for Seasonal Adjustment*

Description

A graphical user interface to the seasonal package and X-13ARIMA-SEATS, the U.S. Census Bureau's seasonal adjustment software. The seasonalview package unifies the code base of <http://www.seasonal.website> with the GUI in the **seasonal** package.

Author(s)

Christoph Sax <christoph.sax@gmail.com>

See Also

[view](#) for the main function of seasonalview.

standalone *Stand Alone Seasonal Web-Application*

Description

Previews a stand alone web application for seasonal adjustment, whith the same look and feel as <http://www.seasonal.website>. Allows import and export of data via an 'Up-/Download' button.

Usage

```
standalone()
```

See Also

[view](#) to interactively modify a "seas" object.

Examples

```
## Not run:  
standalone()  
  
## End(Not run)
```

view

*Interactively Modify a Seasonal Adjustment Model***Description**

Interactively modify a "seas" object. The goal of view is to summarize all relevant options, plots and statistics of a seasonal adjustment model.

Usage

```
view(x = NULL, story = NULL, quiet = TRUE, ...)
```

Arguments

x	an object of class "seas".
story	character, local file path or URL to an ".Rmd" file.
quiet	logical, if TRUE (default), error messages from calls in view are not shown in the console.
...	arguments passed to runApp . E.g., for selecting if the GUI should open in the browser or in the RStudio viewer pane.

Details

Frequently used options can be modified using the drop down selectors in the upper left box. Each change will result in a re-estimation of the seasonal adjustment model. The R-call, the X-13 call, the graphical output and the summary are updated accordingly.

Alternatively, the R call can be modified manually in the lower left box. Click 'Run Call' to re-estimate the model and to adjust the option selectors, the graphical output, and the summary. With the 'To console' button, the GUI is closed and the call is imported to R. The 'Static' button substitutes automatic procedures by the automatically chosen spec-argument options, in the same way as the [static](#) function.

If you are familiar with the X-13 spec syntax, you can modify the X-13 call, with the same consequences as when modifying the R call.

The lower right panel shows the summary, as described in the help page of [summary.seas](#). The 'X-13 output' button opens the complete output of X-13 in a separate tab or window.

If you have the **x13story** package installed (not yet on CRAN, see references), you can call the function with the story argument. This will render an R Markdown document and produce a *story* on seasonal adjustment that can be manipulated interactively.

Value

view returns an object of class "seas", the modified model; or NULL, if the story argument is supplied.

References

Seasonal vignette with a more detailed description: <http://www.seasonal.website/seasonal.html>

Development version of the **x13story** package: <https://github.com/christophsax/x13story>

Examples

```
## Not run:
```

```
m <- seas(AirPassengers)
view(m)
```

```
# store the model after closing the GUI, for further processing in R
m.upd <- view(m)
```

```
## End(Not run)
```

Index

* **package**

seasonalview-package, [2](#)

runApp, [3](#)

seasonalview(seasonalview-package), [2](#)

seasonalview-package, [2](#)

standalone, [2](#)

static, [3](#)

summary.seas, [3](#)

view, [2](#), [3](#)